




Dimension: (Unit: mm)



Motor Connctions



Common Rating

Step angle	1.8°
Position accuracy	18±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100M0hm(500VDC)
Insulation class	B
Temp risel(Max)	80K
Radial play	Max.0.02mm(Load 4.50g)
Axial play	Max.0.08mm(Load 900g)

Specification

Current /phase	1.5 A
Voltage	3.5V
DC Resistance/phase	±10% 2.3Ω
Inductance/phase	±20% 4.3 mH
Holding torque	0.45 N·M
Inertia	0.054 kg·cm <sup>2</sup>
Weight	0.5 kg
Encoder Resolution	1000 cpr

Encoder Signals

颜色	黑	红	白	黄	紫	蓝
定义	EA+	VCC	EGND	EB+	EB-	EA-

设计	王洪松	日期	2018.5.4	材料	深圳市雷赛智能控制股份有限公司 SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.		
审核	秦罕		2018.5.4	第一角画法 First Angle projection	混合伺服电机		
批准	田天胜		2018.5.4	重量Weight	比例Scale	修改标记 Stage Mark	42CME04-PR
图号 Part No.				共 1 套 第 1 套	Sheet 1 of 1	图号 DWG. NO.	LS-CM42-02-0010-03