



技术要求:

- 护线套: 三相 FL75BL
- 信号 FL57BL(S)
- 信号: 十四芯屏蔽线 AWG26#
- 三相: 三芯电缆 YGZF3*0.75mm²
- 耐热硅胶护套 (黑色) 兰黑棕
- HALL 内部接线: 棕灰橙

???	4 poles						
???	1.1ohms±10%(AT 20°C)						
???	2.63mH±20%						
????	24V						
????	4850RPM±10%						
????	<0.5A						
????	0.16N.m						
????	3000±300RPM						
??????	5.55V/KRPM±10%						
????	0.053N.m/A±10%						
WIRE DIAGRAM ?????							
PHASE U	PHASE V	PHASE W	HALL ±5V	HALL 1	HALL 2	HALL 3	HALL GND
?	?	?	?	?	?	?	?

A		使用加卡簧的前盖, 加后罩				DESIGN	DATE	P/N.	
REV	ECN NO.	DESCRIPTION	DRN	APP'D	DATE			TITLE	
		UNLESS OTHERWISE SPECIFIED TOLERANCES:	MATERIAL	CONTR.	CHECK			USED ON	SPECIFICATION
		DECIMALS: .x ±0.5							BLM57050-1000
		ANGULAR: .xx ±0.25 ±0°30'						DWG NO.	REV
		.xxx ±0.1							
		UNIT: mm	THIRD ANGLE PROJECTION	SCALE				雷赛智能控制股份有限公司	
		DO NOT SCALE DRAWING				SHEET 1	OF 2		