



技术要求:

护线套:

三相 FL75BL

信号 FL57BL(S)

信号: 十四芯屏蔽线 **AWG26#**

三相: 三芯电缆 **YGZF3\*0.75mm<sup>2</sup>**

耐热硅胶护套(黑色) 兰黑棕

**HALL** 内部接线: 棕灰橙

??数	4 poles
???	1.2ohms±10%(AT 20°C)
???	3.5mH±20%
????	36V
????	4250RPM±10%
????	<0.5A
????	0.29N.m
????	3000±300RPM
??????	9.1V/KRPM±10%
????	0.087N.m/A±10%
??	<0.75Kg

WIRE DIAGRAM

PHASE U	PHASE V	PHASE W	HALL +5V	HALL 1	HALL 2	HALL 3	HALL GND
?	?	?	?	?	?	?	黑

A	100420	使用加卡簧的前盖, 加后罩				DESIGN	DATE	P/N.	
REV	ECN NO.	DESCRIPTION	DRN	APP'D	DATE			TITLE	
UNLESS OTHERWISE SPECIFIED TOLERANCES:			MATERIAL	CONTR.	CHECK			USED ON	SPECIFICATION
DECIMALS: .X ±0.5								DWG NO.	BLM57090-1000
ANGULAR: .XX ±0.25								REV	
.XXX ±0.1									
UNIT: mm			THIRD ANGLE PROJECTION		SCALE				雷赛智能控制股份有限公司
DO NOT SCALE DRAWING					SHEET	OF			